







| Sensoren        | Niveau  |   |   |  |   | Temperatuur   |
|-----------------|---|---|---|--|---|---|
|                 | Flottersensor   | Druk  | Flotterschakelaar   | Hall   | Capacitatief  |   |
|                 |  |  |  |  |  |  |
| Meetprincipe    | Reed-contacts   | Absoluut of relatief  | Reed-contacts   | Hall effect sensor   | Capacitatief  | 1wire   |
| Nauwkeurigheid  | 21mm  | 10mm  | 100mm   | 20-40mm  | 1-5mm   | 2 °C  |
| Materiaal       | RVS Rubber  | PE -RVC   | RVS Rubber  | Plastic  | Alu - RVS   | Plastic - Alu   |
| Sensor lengte   | 80cm - 160cm  | max. 3m   | max 3m  | nvt  | max 1,6m  | 1,5m  |
| Uitgang signaal | 0-190 Ω   | 0-5V  | 0-105 Ω   | 0-3V   | 0-5V  | 0-3V  |
| ATEX            | NO  | NO  | NO  | NO   | NO  | NO  |
| Fitting         | BSP 5/4"  | 1,5" en 2"  | BSP 3/4"  | nvt  | 1,5"  | nvt   |
| Connector       | 5-pins connector  | 5-pins connector  | nvt   | 5-pins connector   | 5-pins connector  | 5-pins connector  |
| Geschikt voor   | Diesel, Smeerolie, AdBlue, Water, etc   | Diesel, Smeerolie, AdBlue, Water, Chemicalien, etc                                | Diesel, Smeerolie, AdBlue, Water, etc   | Tanks met Butaan - Propaan - LPG gastanks.   | Diesel  | Diverse   |